

# Gear Pullers

**BPL**

Pullers are used for external & internal pulling of gears, bearings etc.

Forged chrome vanadium jaws with long & short reach options

Heat treated alloy steel cross bolt & head for maximum strength

Rolled spindle threads for higher strength & smooth movement even under high stress

Available in two versions:

- a. 2 Jaw models are useful for working in compact spaces
- b. 3 Jaw option ensures equal load distribution to slide gears, pulleys & flywheels off shaft without damage



2 JAW



3 JAW

## ORDERING INFORMATION

CAT NR.	ORD NR.	MAX. REACH		SPREAD RANGE		SAFE WORKING LOAD (TON)	BOX QTY.
		(INCH)	(MM)	(INCH)	(MM)		
<b>2 JAW</b>							
BPL/2J/3	36020	3	75	1 - 7/16	37-75	2	25
* BPL/2J/4	36021	4	100	2 - 4	50-100	4	20
* BPL/2J/6	36022	6	150	3 - 6	75-150	6	10
BPL/2J/8	36023	8	200	4 - 8	100-200	10	6
<b>3 JAW</b>							
BPL/3J/3	36030	3	75	1 - 7/16	37-75	3	25
* BPL/3J/4	36031	4	100	2 - 4	50-100	6	20
* BPL/3J/6	36032	6	150	3 - 6	75-150	9	8
BPL/3J/8	36033	8	200	4 - 8	100-200	15	4

\* Best Seller



3 Jaw Puller used for removing tyre hub