

Lever Grease Gun Dual Piston

G2



The high output greasing solution for applications requiring voluminous and frequent greasing

Built Tough

- Dual piston design 3X output of grease per stroke
- Barrel with 0.049" (1.2 mm) wall thickness
- Heavy duty follower spring
- High tolerance CNC machined Aluminium die-cast head with air release valve
- Rolled threads for quick and easy reloading

Reduce Greasing Time To One-Third

Dual piston mechanism results in triple output per stroke reducing greasing time to one-third

No Loss of Prime

Dual inlet of grease ensures that gun does not lose prime

Convenience of Use

Even in extreme cold weather conditions

Available in 2 choices

- 6" (150 mm) bent steel extension and coupler
- 12" (300 mm) x 0.33" (8.5 mm) flexible hose & coupler

SPECIFICATIONS

DEVELOPS	UPTO 6,000 PSI	UPTO 413 BAR
DELIVERS	UPTO 1 OZ. / 12 STROKES	UPTO 2.4 GM / STROKE

ORDERING INFORMATION

CAT NR.	ORD NR.	CAT NR.	ORD NR.	CARTRIDGE CAPACITY		BULK CAPACITY	THREADS
				(OZ)	(GMS)		
STEEL EXTENSION & COUPLER		FLEXIBLE HOSE & COUPLER					
G2R/B	42630	G2F/B	42640	14	400	500	1/8" BSPT
G2R/M	42631	G2F/M	42641	14	400	500	M10 x 1
G2R/N	42632	G2F/N	42642	14	400	500	1/8" NPT



FILLING OPTIONS

