

# G Clamps General Purpose

GCL



Manufactured from SG iron with a tensile strength of over 60,000 PSI

Handle is designed to bend before the frame is overstressed

Steel main screw has ACME threads


Swivelling pad adopts the correct angle and applies even pressure on the work piece

Textured powder coated finish with spindle in black oxide finish



## SPECIFICATIONS

TENSILE STRENGTH	60,000 PSI	4218 KGF/CM <sup>2</sup>
------------------	------------	--------------------------



## ORDERING INFORMATION

CAT NR.	ORD NR.	CAPACITY (C)		THROAT DEPTH (D)		FRAME PROOF LOAD		BOX QTY.
		(INCH)	(MM)	(INCH)	(MM)	(KGS)	(LBS)	
GCL/13D/50	35807	2	50	1-5/8	42	363	800	40
GCL/13D/75	35800	3	75	1-11/16	44	455	1000	20
* GCL/13D/100	35801	4	100	2-11/32	59	545	1200	20
* GCL/13D/150	35802	6	150	3	75	635	1400	15
GCL/13D/200	35803	8	200	3-1/8	80	775	1700	8
GCL/13D/250	35804	10	250	3-1/2	90	1000	2200	8
GCL/13D/300	35805	12	300	4	100	1135	2500	8

\* Best Seller