Sledge Hammer - DIN 1042
Fibreglass Handle

STFG

NEW!

Head
Forged from fine-grained special steel the heads are induction hardened 50-58 HRC for increased durability

Handle
Lightweight yet durable dual injection moulded fibreglass handle for controlled and balanced swing

Designed with a 25% wider neck, handles are covered with a polypropylene jacket for protection against overstrikes

TPR grip on handle absorbs shock and vibration and provides a non-slip grip

Handles securely attached to the hammer head using a tough epoxy adhesive ensuring that the head does not fly away even with rough use

UTILITY

- Light demolition work
- Cutting stone & concrete
- Masonry

ORDERING INFORMATION

CAT NR.	ORD NR.	HEAD WEIGHT		OVERALL LENGTH		BOX QTY.
		(GMS)	(KG)	(INCH)	(MM)	
STFG/DIN/3K/24	36550	3000	3	24	600	4
STFG/DIN/4K/28	36551	4000	4	28	700	4
STFG/DIN/5K/32	36552	5000	5	32	800	4
STFG/DIN/6K/32	36553	6000	6	32	800	4
STFG/DIN/8K/36	36554	8000	8	36	900	4

WARNING

Do not strike objects harder than 46 HRC. Striking items of a greater hardness is liable to cause fracture or chipping